

# R5


## Ribbon to Ribbon

### BENEFITS AND FEATURES

- Remote maintenance via Internet
- Integrated 5 function in one unit (stripping, cleaning, cleaving, splicing, protecting)
- The fusion splicer with All-In-One™ system provides the best workability on the pole and also in the limited work space.
- No scratches on fiber by thermal stripping
- 4.3-inch color LCD monitor with touch screen & bidirectional operation system
- Powerful Lithium Polymer Battery with large capacity
- Resistance to shock, dust and water
- Built-in dual sleeve heater
- Equipped with sleeve loader for easy fiber loading for ribbon fiber



ALLINONE



ROTATING BLADE LIFE  
Up to **75,000**



ELECTRODE LIFE  
Up to **1,500**



MPO SOC



STRIPPING



CLEAVING



CLEANING



Ribbonizing Holder Kit



## SPECIFICATION

CATEGORY	DESCRIPTION
Fiber alignment	Fixed V-Groove(Clad to Clad)
Applicable type of fibers	SM(ITU-T G.652), MM(ITU-T G.651), DS(ITU-T G.653), NZDS(ITU-T G.655), ITU-T(G.657)
Fiber count	Single fiber, 2~12 fiber
Applicable fiber dimensions	Single: Cladding diameter 125 $\mu$ m, Coating diameter 250, 900 $\mu$ m Ribbon: Cladding diameter 125 $\mu$ m, Ribbon fiber thickness 0.27 to 0.32mm
Fiber setting and cleaved length	0.31in
Splicing modes	Splice mode: 100, Heat mode: 50
Typical splice Loss	SM: 0.05dB, MM: 0.02dB, DS: 0.08dB, NZDS: 0.08dB
Return loss	> 60dB
Splicing time	Typical 20sec with standard SM(ITU-T G.652)
Splice loss estimate	Available
Sleeve heating time	30sec, 50sec
Applicable protection sleeve	1.5in, 2.4in (fiber), 1.1in or 1.3in (Connector)
Storage of splice result	The last 10,000 results to be stored in the internal memory.(Image 10,000 results)
Tension test	2N / 4,4N(Optional)
Operating condition	Altitude: 5,000m above sea level, Temperature: -14 $^{\circ}$ F~122 $^{\circ}$ F, Humidity: 0~95%, Wind: 15m/s, non-condensing, dust proof, water proof, shock proof
Storage condition	Temperature:-40 $^{\circ}$ F~176 $^{\circ}$ F, Humidity: 0~95%
Dimension	5.6(W) x 8.9(L) x 5.2(H)in (Including rubber)
Weight	5.5lb (Including battery 7.1lb)
Viewing method and display	Two CMOS cameras and 4.3-inch color LCD monitor with touch screen
Fiber view and magnification	50X
Power supply	DC Lithium polymer battery(DC 14.8V, 8400mAh), 100~240V AC Adapter
No. of splice cycles with battery	320cycle
Electrode life	More than 1,000 times
Terminals	USB, External power(DC 12V Available for car cigar jack)

## STANDARD PACKAGE

CATEGORY	MODEL	Q'ty
Arc Fusion Splicer	R5	1
AC Adapter	F1-1	1
Sleeve Loader	S312	2
Spare Electrode	EI-22	1 pair
Battery Pack	S513	1
Cooling Tray	CT-03(60mm)	1
Holder	H7-12	1 pair
Tool Box	-	1
User Manual	-	1
Carrying Case	Hard Case	1
Allen wrench	-	1
Soft brush	-	1

## OPTION PACKAGE

CATEGORY	MODEL
Battery Pack	S513
Cleaver Blade	BI-07
Electrode	EI-22
Fiber Holder	H7-12, H7-10, H7-8, H7-6, H7-4, H7-2, H7-250, H7-900, H7-IN, H7-2.5
Sleeve	R-F40(40mm)
Sleeving Clamp	SC-01
External Power	DC 12V Available for car cigar jack

**COVERTEL**  
TELECOMMUNICATIONS GROUP

### Need local support?

Contact: Brad Wilmore  
Email: brad@covertel.com.au  
Mobile: +61 433 115 101 Office: 03 9381 7888

**Get quick assistance without international delays.**