

**COVERTEL**  
 TELECOMMUNICATIONS GROUP

**Need local support?**

 Contact: Angelo Monteleone  
 Email: [angelo@covertel.com.au](mailto:angelo@covertel.com.au)  
 Mobile: +61 430 508 509 Office: 03 9381 7888

**Get quick assistance without international delays.**

**FC-220**

Designed to cleave either 900 $\mu$ m buffered or 250 $\mu$ m coated fiber, this fiber cleaver's quick and easy three step operation is perfectly suited for mechanical splicing and quick field termination of fiber connectors. This fiber cleaver features the following:

- Leaf spring scale is ruled to allow accurate and precise cleave lengths from 2 to 20mm (0.079" to 0.79")
- Ultra-strong carbide blade will last up to 6,000 cleaves before needing to be replaced
- Handles both single and multi-mode fibers with 125 $\mu$ m cladding
- Replacement Parts: FC-4 Replacement Blade and FC-65 Replacement Leaf Spring

**SPECIFICATIONS**

<b>CLEAVE LENGTH</b>	2.0mm to 20.0mm (0.079" to 0.79")
<b>DIMENSIONS</b>	4.89" x 0.787" x 1.57" (124mm x 20mm x 40mm)
<b>OPERATING TEMPERATURE</b>	0 to 40 deg. C
<b>STORAGE TEMPERATURE</b>	-20 to 60 deg. C
<b>WEIGHT</b>	0.132 lbs (59.87g)
<b>UPC NO.</b>	811490017078

**MADE FOR LIFE®**